



Sanitary Design Questionnaire

APV Paratube Tubular Heat Exchangers

To obtain a quotation, please provide as much detail as possible and e-mail to phequotes@apv.com or fax to 716-692-0130.

CONTACT INFORMATION		
Date:	Your Reference:	
Company:	Title:	
Address:	Phone:	
City:	Fax:	
State, Zip:	Email:	
APPLICATION DETAILS		
Type of Quote:	<input type="checkbox"/> Firm <input type="checkbox"/> Budget <input type="checkbox"/> Magnitude of Cost	
Quote Due Date: _____	Approximate Installation Date: _____	
Description & Chemical Composition	Product	Service
Name of Fluid		
Rate of Flow GPM		
Inlet Temperatures °F		
Pasteurization Temperature °F		
Outlet Temperature °F		
Maximum Permissible Pressure Drop PSI		
Maximum Working Pressure PSI		
Specific Gravity		
Specific Heat at Mean Temperature		
Thermal Conductivity at mean Temperature		
Viscosity at Inlet Temperature cps		
Viscosity at Outlet Temperature cps		
Total Solids %		
Particulates (max size and percentage)		
Nature of Solids (i.e. fibrous, powder, size)		
Flow Fluctuations, if any		
Preferred Plate Material	<input type="checkbox"/> 304L SS <input type="checkbox"/> 316L SS <input type="checkbox"/> Titanium <input type="checkbox"/> Other: _____	
Available Space (L x W x H in feet)		
Note: standard lengths are typically 22 feet		
COMMENTS		

APV, An SPX Brand, 105 CrossPoint Parkway, Getzville, NY 14068
 Phone: (716) 692-3000 Fax: (716) 692-0130 Email: phequotes@apv.com

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.apv.com.
 SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation.
 Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 06/2009 1201-01-06-2009-US

Copyright © 2009 SPX Corporation

