



Sanitary Design Questionnaire

APV PARATUBE TUBULAR HEAT EXCHANGERS

To obtain a quotation, please provide as much detail as possible and e-mail to phequotes@apv.com or fax to 716-692-0130.

CONTACT INFORMATION		
DATE:	YOUR REFERENCE:	
COMPANY:	TITLE:	
ADDRESS:	PHONE:	
CITY:	FAX:	
STATE, ZIP:	EMAIL:	
APPLICATION DETAILS		
TYPE OF QUOTE: <input type="checkbox"/> FIRM <input type="checkbox"/> BUDGET <input type="checkbox"/> MAGNITUDE OF COST		
QUOTE DUE DATE:		APPROXIMATE INSTALLATION DATE:
DESCRIPTION & CHEMICAL COMPOSITION	PRODUCT	SERVICE
NAME OF FLUID		
RATE OF FLOW	GPM	
INLET TEMPERATURES	°F	
PASTEURIZATION TEMPERATURE	°F	
OUTLET TEMPERATURE	°F	
MAXIMUM PERMISSIBLE PRESSURE DROP	PSI	
MAXIMUM WORKING PRESSURE	PSI	
SPECIFIC GRAVITY		
SPECIFIC HEAT AT MEAN TEMPERATURE		
THERMAL CONDUCTIVITY AT MEAN TEMPERATURE		
VISCOSITY AT INLET TEMPERATURE	CPS	
VISCOSITY AT OUTLET TEMPERATURE	CPS	
TOTAL SOLIDS	%	
PARTICULATES (MAX SIZE AND PERCENTAGE)		
NATURE OF SOLIDS (I.E. FIBROUS, POWDER, SIZE)		
FLOW FLUCTUATIONS, IF ANY		
PREFERRED PLATE MATERIAL <input type="checkbox"/> 304L SS <input type="checkbox"/> 316L SS <input type="checkbox"/> TITANIUM <input type="checkbox"/> OTHER:		
AVAILABLE SPACE (L X W X H IN FEET) NOTE: STANDARD LENGTHS ARE TYPICALLY 22 FEET		
COMMENTS		

SPX Flow Technology, 105 CrossPoint Parkway, Getzville, NY 14068
Phone: (716) 692-3000 Fax: (716) 692-0130 Email: phequotes@apv.com



SPX reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit www.spx.com.