



APV Homogeniser

Cube 4600/ Cube 5800

Introduction:

- The CUBE 4600/5800 homogeniser, a positive-displacement triplex, reciprocating plunger pump, is fitted with a two-stage homogenising valve assembly with manual actuation.

Drive system:

- The power is transmitted from the 37 kW motor via V-belts and pulleys to the crankshaft.

Crankcase:

- High quality cast iron housing. Crankshaft and cross-heads are forced lubricated to ensure long life.

Control system:

- The CUBE is a plug-and-play solution equipped with Y/D starter and is fully controlled with start/stop buttons and emergency stop situated on the front panel.

Liquid End:

- Pump valve housing in HQ-SS with Stellite ball valves and Stellite valve seats.
- The two-stage homogenising arrangement is manually adjusted with plug and piloted valves, as well as pressure gauge for total pressure indication.
- 51 mm tri-clamp flanges for inlet and outlet connection.

Housing:

- Stainless steel cladding.

Technical data:

- Service media: Water: 120 l/h for lubrication of plungers and cooling of oil in oil sump.

Oil:

- Standard ISO VG 220 lubrication oil is used in oil sump.

Type	Maximum Capacity l/h	Maximum Pressure bar	Plunger Ø mm
4600	4,600	250	45
5800	5,800	200	50

Crankshaft speed at max. flow:	210 rpm
Overall dimensions in mm (LxWxH):	1863 x 1110 x 1598
Service area in mm (LxWxH):	2863 x 3110 x 2000
Shipping details:	Net weight 1690 kgs
	Export packing 2085 kgs
	Shipping volume 7.06 m3

APV, An SPX Brand, Roholmsvej 8, DK-2620 Albertslund, Denmark
Phone: +45 70 278 999 Fax: +45 70 278 998

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.apv.com.
SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation.
Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.