



APV DuoSafety

APV DuoSafety* Plate Heat Exchanger

The APV DuoSafety heat exchanger plate pair differs from previously known double-wall types. The new APV DuoSafety heat exchanger plate pairs have a great advantage of being completely weld-free.

Design and Construction

The APV DuoSafety plate consists of two loose heat exchanger plates. These can be made of different material, each plate pair is fitted with a non glued Paraclip or EasyClip gasket, which both seals and holds the pair together. Gaskets can be supplied in a full range of materials. The use of two plates in this manner provides added safety against the possibility of any through-plate leakage, since any cracks or corrosion damage in a plate will cause leakage into the space between each DuoSafety plate pair. Should a leakage occur, the liquids will not be mixed since the leaking liquid will flow between the plate pair faces to the atmosphere, where it will be visible as an indication that corrective action should be initiated.

Advantages of Using

APV DuoSafety Plate Pairs

There are many advantages of using the new APV DuoSafety plate heat exchanger:

- 100% visual inspection is possible
- The APV DuoSafety plate pair can be dismantled for cleaning and inspection

- It is possible to combine different plate materials in one plate pair
 - Such as stainless steel/titanium or Hastelloy**/titanium
 - Two gasket materials can be combined e.g. EPDM/Nitrile
- High safety against mixing of fluids
- Completely weld-free

These are only a few of the many advantages obtained by using the APV DuoSafety plate.

Industries Served

The APV DuoSafety plate heat exchanger can advantageously be used within numerous industries, such as:

- Pharmaceutical
- Nuclear
- Chemical
- Food
- Petrochemical
- HVAC heating of utility water

* Patented


**Hastelloy is a registered trademark of Haynes International

Range of Materials

The APV DuoSafety heat exchanger plate pairs can be supplied in stainless steel, higher nickel alloys, titanium, etc. or by combining different plate materials in one plate pair. Gaskets are now available in NBR or EPDM material.

Your Supplier

APV introduced the plate heat exchanger in 1923 and has since been a market leader. In 1986 a factory was built in Kolding, Denmark, followed two years later by a factory in Goldsboro, North Carolina, USA. Today, we continue to lead the industry with our world renowned state-of-the-art technology, unsurpassed process knowledge and an unwavering commitment to our customers.



Your local contact:



APV, An SPX Brand
1200 West Ash Street, Goldsboro, NC 27530
Phone: (919) 735-4570 Fax: (919) 581-1167
Email: answers.us@apv.com

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.apv.com.

SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 08/2008 1018-02-08-2008-US Copyright © 2008 SPX Corporation

SPX
WHERE IDEAS MEET INDUSTRY